



IceLED



ø99 x H45 / 55 (mm)
Rth 0.58 - 0.46 °C/W
Power Pd 85.5 - 109 W

[MORE PRODUCT DETAILS](#)

IceLED | Bridgelux Modular Active Star LED Cooler ø99mm



Mounting Instruction



Bridgelux is a leading provider of high power, cost effective and energy efficient light emitting diode (LED) solutions. Leveraging patented light source technology, Bridgelux LED Arrays replace traditional technologies (such as incandescent, halogen, fluorescent and high intensity discharge lighting) with integrated solid state light sources enabling high performance and energy-efficient products for the general lighting market.

Mounting indicator marks overview

MechaTronix recommends the use of a high thermal conductive interface between the LED module and the LED cooler. Either thermal grease, a thermal pad or a phase change thermal pad thickness 0.1-0.15mm is recommended. Thermal pads or phase change thermal pads can be pre-applied from MechaTronix.



Bridgelux Gen 7 V series V22 LED Array

Model names

- BXRE-xxx650x-x-7x

Mounting

- With Zhaga Book 3 LED holder
- BJB spotlight connector 47.319.2030
- Ideal Industries Chip-Lok™ holder 50-2204CT
- Bender+Wirth 431 Typ 2
- Mounting with 2 self tapping screws M3 x 10mm
- Green indicator marks