

## IceLED Ultra VS | Vossloh Schwabe Modular Active Star LED Cooler ø99mm

### Features & Benefits

- For spot and downlight designs from 14,500 to 29,000 lumen
- Thermal resistance range Rth 0.26°C/W
- Modular design with mounting holes foreseen for Vossloh Schwabe Luga Industrial WU-M-467/443, Luga Shop WU-M 485/486/462/464, direct with just a few screws.
- Diameter 99mm - Standard height 75mm  
Other heights on request
- High lifetime design >60Khrs (L 10 life time @40°C)
- Warranty 5 years



### Order Information

Zhaga

VS LIGHTING SOLUTIONS

Example : IceLED Ultra VS

IceLED 1

1 Ultra VS

Simple mounting with self tapping screws  
Recommended screw force 6lb/in  
Screws are available from MechaTronix

## IceLED Ultra VS Modular Active Star LED Cooler ø99mm

### Product Details



*IceLED Ultra VS*

#### Model n°

Dimension (mm) <sup>*1</sup>	ø99 x h75
Fan Voltage (Vdc) <sup>*2</sup>	12
Fan Speed (RPM)	2600
Noise @ 1m (dBA)	<35.6
Weight (gr)	425
Thermal Resistance (°C/W) <sup>*3</sup>	0.26
Power Pd (W) <sup>*4</sup>	150
Heat Sink Material	AL6063-T5

<sup>\*1</sup> 3D files are available in ParaSolid, STP and IGS on request

<sup>\*2</sup> The fan requires a constant voltage power source of 12Vdc, 160mA, 1.8W

<sup>\*3</sup> The thermal resistance Rth is determined with a calibrated heat source of 30mm x 30mm central placed on the heat sink, Tamb 40° and an open environment. Reference data @ heat sink to ambient temperature rise Ths-amb 50°C  
 The thermal resistance of a LED cooler is not a fix value and will vary with the applied dissipated power Pd

<sup>\*4</sup> Dissipated power Pd. Reference data @ heat sink to ambient temperature rise Ths-amb 50°C  
 The maximal dissipated power needs to be verified in function of required case temperature Tc or junction temperature Tj and related to the estimated ambient temperature where the light fixture will be placed  
 Please be aware the dissipated power Pd is not the same as the electrical power Pe of a LED module

To calculate the dissipated power please use the following formula:  $Pd = Pe \times (1 - \eta_L)$

Pd - Dissipated power

Pe - Electrical power

$\eta_L$  = Light efficiency of the LED module

#### Notes:

- MechaTronix reserves the right to change products or specifications without prior notice.
- Mentioned models are an extraction of full product range.
- For specific mechanical adaptations please contact MechaTronix.