

ø99 x H55 (mm)
 Rth 0.46 °C/W
 Power Pd 109 W

[MORE PRODUCT DETAILS](#)

IceLED Xtra | Lumileds Modular Active Star LED Cooler ø99mm



Mounting Instruction



Lumileds LUXEON COB is a new breakthrough in efficacy for arrays. Due to its industry leading small Light Emitting Surfaces (LES), the COB array is very easy work with and will enable easier and less expensive designs. All LUXEON COBs are available in a single 3-step as well as a single 5-step MacAdam Ellipse, ensuring uniform optical performance in the application. Ideal applications include down lights and directional lamps.

Mounting indicator marks overview

MechaTronix recommends the use of a high thermal conductive interface between the LED module and the LED cooler. Either thermal grease, a thermal pad or a phase change thermal pad thickness 0.1-0.15mm is recommended. Thermal pads or phase change thermal pads can be pre-applied from MechaTronix.



Luxeon Gen 4 Luxeon CoB Core Range 1812

Model names

- L2C5-xxxx1812G2300

Mounting

- With Zhaga Book 3 LED holder
- BJB spotlight connector 47.319.2030
- Ideal Industries Chip-Lok™ holder 50-2204CT
- Mounting with 2 self tapping screws M3 x 8mm
- Green indicator marks