

ø152 x H100 / 150 (mm)  
Rth 0.52 - 0.46 °C/W  
Power Pd 95 - 110 W

**MORE PRODUCT DETAILS**

## ModuLED Giga-HBG | Osram Soleriq High Bay LED Cooler ø152mm with driver connection system


### Mounting Instruction



Osram SOLERIQ® LEDs are designed to meet the requirements of professional indoor general lighting applications. Large flux output, small light emitting surfaces, variation, CRI greater than 80 and easy to use Chip-on-Board technology support easy and creative lighting design. These properties make SOLERIQ® LED COB modules a high efficient, high-quality and price-performance-optimized solution for all demanding and at the same time cost-conscious lighting manufactures and designers.

#### Mounting indicator marks overview

MechaTronix recommends the use of a high thermal conductive interface between the LED module and the LED cooler. Either thermal grease, a thermal pad or a phase change thermal pad thickness 0.1-0.15mm is recommended. Thermal pads or phase change thermal pads can be pre-applied from MechaTronix.



#### Osram Soleriq P13 LED COB

##### Model names

- GW MAGMB1.EM
- GW MAGMB1.CM

##### Mounting

- With Zhaga Book 3 LED holder
- Ideal Industries Chip-Lok™ holder 50-2101CR
- Mounting with 2 screws M3 x 6mm
- Green indicator marks



#### Osram Soleriq S19 LED COB

##### Model names

- GW-KAHLB1-xxxx

##### Mounting

- With Zhaga Book 3 LED holder
- BJB spotlight connector 47.319.2170
- TE Connectivity Lumawise type Z50 2213407-1
- TE Connectivity Lumawise type Z50 2213407-2
- Mounting with 2 screws M3 x 6mm
- Green indicator marks

