

ModuLED Mega | Tridonic Talexxx Modular Passive Star LED Cooler ø134mm

Features & Benefits

- The ModuLED Mega modular passive LED coolers are specifically designed for luminaires using Tridonic Talexx COB and LED modules. Mechanical compatibility with direct mounting of the LED modules to the LED cooler and thermal performance matching the lumen packages.
- For spot and downlight designs from 3,700 to 14,300 lumen
- Thermal resistance range Rth 0.67 - 1.32°C/W
- Modular design with mounting holes foreseen for Tridonic TALEXXmodule DLE GEN2/Gen 3/Gen 4 ADV 65mm, SLE Gen 5 15/19/23mm, Gen 6 19/23mm, Gen 6 15/17mm D50, G6 19/23mm FOOD EXC, G6 15/17/19/23mm FASHION EXC, G6 19/23mm ART EXC, G7 ADV 15/17/21mm LED COB, direct mounting or by LED holder.
- Diameter 134mm - Standard height 20mm & 50mm & 100 mm Other heights on request
- Extruded from highly conductive aluminum



Order Information



TRIDONIC

Example : ModuLED Mega 134100-B

ModuLED Mega 134 **1** - **2**

- 1** Height (mm)
- 2** Anodising Color
 B - Black
 C - Clear

Simple mounting with self tapping screws
 Recommended screw force 6lb/in
 Screws are available from MechaTronix

