

## LPF11180-ZHE Luminus Pin Fin LED Cooler $\phi$ 111mm

### Features & Benefits

- The LPF11180-ZHE Zhaga Pin Fin LED cooler is specifically designed for luminaires using Luminus COB LED arrays. Mechanical compatibility with direct mounting of the LED modules to the LED cooler and thermal performance matching the lumen packages.
- For spot and downlight designs from 4,800 to 9,600 lumen
- Thermal resistance Rth 1.07°C/W
- Modular design with mounting holes foreseen for Luminus Gen4 CIM-14/22, CLM-14/22, CXM-14(AC)/18/22, CGM-14, Gen3 CXM-14(AC)/18(AA)/22(AC), CLM-22(AC) LED COB by use of LED holder.
- Diameter 111mm - Height 80mm  
Other heights on request
- Better performance under tilted position
- Forged from highly conductive aluminum



### Order Information



Example : LPF11180-ZHE-B

LPF11180-ZHE- **1**

- 1** Anodising Color  
B - Black  
C - Clear  
Z - Custom ( specify )

Simple mounting with M3 screws  
Screws are available from MechaTronix

## LPF11180-ZHE Zhaga Pin Fin LED Cooler ø111mm

### Product Details



**Model n°**

**LPF11180-ZHE**

Dimension (mm) <sup>*1</sup>	ø111 x h80
Volume (mm <sup>3</sup> )	211924
Cooling Surface (mm <sup>2</sup> )	116830
Weight (gr)	572
Thermal Resistance (°C/W) <sup>*2</sup>	1.07
Power Pd (W) <sup>*3</sup>	50
Heat Sink Material	AL1070

<sup>\*1</sup> 3D files are available in ParaSolid, STP and IGS on request

<sup>\*2</sup> The thermal resistance Rth is determined with a calibrated heat source of 30mm x 30mm central placed on the heat sink, Tamb 40° and an open environment. Reference data @ heat sink to ambient temperature rise Ths-amb 50°C  
The thermal resistance of a LED cooler is not a fix value and will vary with the applied dissipated power Pd

<sup>\*3</sup> Dissipated power Pd. Reference data @ heat sink to ambient temperature rise Ths-amb 50°C  
The maximal dissipated power needs to be verified in function of required case temperature Tc or junction temperature Tj and related to the estimated ambient temperature where the light fixture will be placed  
Please be aware the dissipated power Pd is not the same as the electrical power Pe of a LED module

To calculate the dissipated power please use the following formula:  $Pd = Pe \times (1 - \eta_L)$

Pd - Dissipated power

Pe - Electrical power

$\eta_L$  = Light efficiency of the LED module

#### Notes:

- MechaTronix reserves the right to change products or specifications without prior notice.
- Mentioned models are an extraction of full product range.
- For specific mechanical adaptations please contact MechaTronix.