

LPF4768-ZHP Osram PrevaLED Pin Fin LED Cooler ø47mm


Mounting Instruction



With the PrevaLED Core and PrevaLED Core AC, Osram leads the path of versatile LED light modules interchangeable according Zhaga book 3 specifications. With an initial color binning below 3 steps Mc Adam, a wide range of lumen packages from 1.100lm all the way up to 5.000lm and a broad availability of color temperatures, the Osram PrevaLED Core found it's strive in high-end shop and down light applications with an uncompromised lighting quality.

Mounting indicator marks overview

MechaTronix recommends the use of a high thermal conductive interface between the LED module and the LED cooler. Either thermal grease, a thermal pad or a phase change thermal pad thickness 0.1-0.15mm is recommended. Thermal pads or phase change thermal pads can be pre-ap



Osram PrevaLED Core AC G2

Model names

- PL-CORE AC -800-xxx
- PL-CORE AC -2000-xxx

Mounting

- Direct mounting with 2 screws M3 x 8mm
- Green indicator marks

Osram PrevaLED Core G7 L10 H1

Model names

- PL-CORE-G7 1000-xxx L10 H1
- PL-CORE-G7 2000-xxx L10 H1

Mounting

- Direct mounting with 2 screws M3 x 8mm
- Orange indicator marks

Osram PrevaLED Core G7 L15 H1

Model names

- PL-CORE-G7 2000-xxx L15 H1
- PL-CORE-G7 3000-xxx L15 H1

Mounting

- Direct mounting with 2 screws M3 x 8mm
- Green indicator marks

Osram PrevaLED Core G7 Food / Fashion

Model names

- PL-CORE-G7 2000-927 L15 H1
- PL-CORE-G7 2000-Sxxx L15 H1

Mounting

- Direct mounting with 2 screws M3 x 8mm
- Green indicator marks